

TEST ATTESTATION

Contract No.: 2571/2014/54/1 - RT

03.08.2015
NEF/RIK

Customer: Kaindl Flooring GmbH
Kaindlstraße 2
AT-5071 Wals/Salzburg

Subject: Laminate floor No. 54 of the type:
„Kaindl Laminate FLOORING Natural Touch 10.0 Narrow Plank“
Test according to OENORM EN 13329 „Laminate floor coverings - Specifications, requirements and test methods“


Result:

Classification requirements		
Wear resistance	AC4	
Impact resistance	IC2	
Resistance to staining	Group 1 and 2	level 5
	Group 3	level 4
Resistance to cigarette burns	level 4	
Effect of a furniture leg	no damage is visible	
Effect of a castor chair	no damage is visible	
Thickness swelling	≤ 18,0 %	


The tested laminate floor fulfils all requirements of OENORM EN 13329 for the level of use classes 32. The formaldehyde release determined according to OENORM EN 717-2 is below the allowable limit for faced wood-based panels which is given in the Austrian formaldehyde regulation and in DIBt-Guideline 100 (E1). Since 01.01.2009 only substrates certified according to CCR, Title 17 93120.2(a) Phase 2 (CARB Regulation) are used by the manufacturer. Usage and conformity of the substrates are subject to regular tests and plant audits by Holzforschung Austria (CARB TPC-11). Measured contents of the respective heavy metals, chrome VI and organic tin compounds were below the requirements of OENORM EN 71-3. The formaldehyde emission determined according to the desiccator method (JIS A 1460) met the limit value of ≤ 0,3 mg/l.

Period of validity: June 2016

HOLZFORSCHUNG AUSTRIA



DL Georg Oberdorfer
Technical consultant



DI Franz Neumüller
Technical consultant

In case of dispute the original German version prevails. This translation is for information purposes only.